

Multi-Purpose Adhesive Sealant



Adheres To

- Vinyl
- Brick
- Fiberglass
- Aluminum
- RV
- Concrete
- Masonry
- Wood
- Stone
- Marine
- Fiber Cement
- Steel
- Ceramics
- Building Paper
- Single-Ply

Product Advantages

- Waterproof, Premium All-Weather Silicone
- Excellent Tooling Characteristics
- Service Temperature -40 F to +400 F
- Application Temperature -20 F to +120 F
- UV and Mildew Resistant
- Permanently Flexible
- Will Not Shrink, Crack, Sag or Slump
- Weather Tight Seal
- Low Odor
- Solvent Free
- Invisible to UV Light
- Easily Gunned at all Temperatures




White
M100



Blue White
M101



Antique White
M105



Canvas
M107



Black
M110



Gray
M111



Dark Bronze
M120



Lincoln Bronze
M121



Imperial Brown
M130



Earthtone
M132



Terratone
M134



Dark Sand
M138



Beige
M140



Tan
M141




Almond
M143



Sandstone
M146



Translucent
M150



Forest Green
M162

Product Information

- Description - Multi-Purpose Adhesive Sealant
- Item Number - 02-MX0XXXX-10C1
- Size - 10.3 FL. OZ (304 mL)
- Unit Dimensions - 9" X 2" X 2"

Also available in sausage packages:

Item Number - 02-MX0XXXX-20S1

Size - 20 FL Oz

Dimensions - 12 3/4" x 2" (unit)

13 1/2" x 8 1/4" x 6" (case)

Case Pack Information

- Description - Multi-Purpose Adhesive Sealant
- Item Number - 02-MX0XXXX-10C1
- Dimensions - 11 15/16" X 9 15/16" X 8 1/8"
- Case Weight - 10 lbs - 12 packs
20 lbs - 24 packs
- Cases Per Pallet - 60 - 24 packs
120 - 12 packs

Over 60 colors available for siding, fiber cement, roofing gutters, coil & trim

Multi-Purpose Adhesive Sealant

Technical Information

Product: Novaflex Multi-Purpose Sealant
 Appearance: Smooth paste
 Application Temperature: -20 °F to +120°F (-28°C to 50°C)
 Service Temperature: -40°F to +400°F (-40°C to 200°C)
 Adhesion: Excellent to most common building materials
 Consistency: Non-sag
 Bridging Ability: Excellent, bridges gaps to 3/4" (2 cm)
 Gunning Extrusion: Very easy to gun and clean up
 Durability: +/- 25% joint movement
 Flexibility: Remains flexible to -40°F
 Water Resistance: Excellent – Not to be submerged
 Exterior Weathering: Excellent
 Aging: Excellent
 Freeze-Thaw Stable: Will Not Freeze
 Odor: None
 Skin Time:

- 40°F/40% relative humidity – 40 minutes
- 75°F/50% relative humidity – 10 minutes
- 95°F/95% relative humidity – 5 minutes

 Through and Cure Time:

- 40°F/60% relative humidity – 2-3 days
- 75°F/50% relative humidity – < 24 hrs

 Weight per gallon: 10.2 pounds
 Solids: 97%
 Flash Point: > 400°F

Novaflex[®] Multi-Purpose Adhesive Sealant is a premium all-weather medium modulus silicone that stays flexible and resistant to cracking and discoloration. Cured sealant resists mildew. This premium all-weather silicone is tack free in 10 minutes and is completely cured in up to 2 days. Cure time is with above 30% relative humidity and varies with temperature and humidity.

Product Specs

Coverage: 28 linear ft. using a 1/4" bead or 14 linear ft. using a 3/8" bead.

Specifications: Meets or exceeds the performance characteristics of: ASTM C-920, AAMA 802.3, 805.2, 808.3, TT-S-001543A and TT-S-230C.

Shelf life: Use product within 18 months from manufacturers date. FREEZE THAW STABLE. Store product at 40°F to 80°F.

MAX VOC: less than 34 g/l (<4% by weight). VOC compliant in all 50 states.

Recommended For Sealing

- Windows
- Door Sills
- Gutters
- Doors
- Flashing
- Nail Fins
- Metal Roofs
- Cap Beading
- Fiber Cement
- Head Expanders
- Reglazing Broken/Defective Glass
- Vinyl Siding
- Trim Coil

Not Recommended For

- Joints continuously submerged under water
- Areas needing paint or stain
- Spaces confined from atmospheric moisture during cure
- On surfaces that might bleed oils, plasticizers or solvents
- In structural glazing applications
- Painted Applications

Limited Warranty: Satisfaction guaranteed when handled and applied according to label instructions. Call 1-800-380-0138 for Customer Service.

CAUTION! Methyl ethyl ketoxime, methyl and thyl alcohol released during cure. Avoid breathing vapors. Avoid prolonged or repeated skin contact.

KEEP OUT OF REACH OF CHILDREN

First Aid: Skin: Wash with soap and water. Eyes: SEEK IMMEDIATE MEDICAL ATTENTION. Inhalation causing discomfort: Remove to fresh air. If discomfort persists or any breathing difficulty occurs, or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. Additional information please refer to MSDS.

Disposal: For disposal of material follow federal, state and local regulations.



NOVAGARD
 Solutions.
 Engineered Products... Innovative Thinking

5109 Hamilton Ave.
 Cleveland, OH 44114
 1-800-380-0138
 www.novagard.com
 Made in USA. For commercial use.